

# Cooperation for Vehicular Delay Tolerant Network

Adnan Muhammad  
Institute of Telecommunication  
Politehnica University Bucharest,  
Bucharest, Romania.  
admu05@lmn.ro

Tauseef Jmal  
SITILabs,  
University Lusofona,  
Lisbon, Portugal.  
tauseef.jamal@ulusofona.pt

**Abstract**—This article reviews the literature related to Vehicular Delay Tolerant Network with focus on Cooperation. It starts by examining definitions of some of the fields of research in VDTN. An overview of VDTN with cooperative networks is presented.

**Keywords-component;** Cooperative Networks, Vehicular Delay Tolerant Network, Cooperation.

## Introduction

This survey will present cooperation for VDTN and how those systems incorporate cooperation. VDTN gathers contributions from opportunistic and cooperative networks as a communication infrastructure for the network to carry and disseminate data. Data communication in VDTN presents new challenges when compared with other kinds of network. VDTN network can be partitioned. This results in a few transmission opportunities and unpredictable delays [3].

Running internet protocol performs transmission control protocol/internet protocol making implicit assumptions of continuous, path short round trip and symmetric data rates. Although wide range of emerging networks usually referred to opportunistic networks connected networks, or episodic networks violate these assumptions.

Delay tolerant networking is a network research topic focus on the design implementation, evaluation and application of architectures that intend to enable data communication among heterogenous networks in an environment [6].

Vehicular delay tolerant networking appears as a novel network architecture that provide innovative solutions for challenging vehicular communication.

Effective operation of DTNs and VDTNs relies on the cooperation of network nodes to store-carry-and-forward data over partitioned and challenged network environments [6].

We would like to advise that the oen of the focus in this area should be to provide a mathematical framework for studying user cooperation in an ad hoc networks, and to define strategies leading to an optimal user behavior.

Cooperation is the basic characteristic of multiagent system, while cooperation structure is central to the study of multiagent cooperation. At present, all the previous studies focus on the description to the negotiation, the conflict, the benefit distribution, the cooperation process and the cooperation evolution with game theory or multimodal theory and, very little is known about the analysis of the multiagent cooperation structure. Two kinds of multiagent cooperation structures were provided in literature the complete cooperation structure and the incomplete structure, but the objective exchanging and the number of both sides were neglected. This paper begins with an introduction of the current status of research on the multiagent cooperation and definition of multiagent cooperation, then sixteen cooperation structures are provided according to the three dimensions, whether cooperation is complete, whether the objective exchanging of both sides exists, and the number of both sides. Furthermore, a set of communication primitives is designed for multiagent cooperation [8].

User-cooperation or relaying through other nodes is an efficient approach to obtain diversity in wireless networks. In this paper, we consider a coded cooperative system under quasi-static Rayleigh fading to find conditions on the inter-user and user-to-destination channel qualities for cooperation to be beneficial. We define the user cooperation gain as the gain in frame error rates due to cooperation when a particular channel code is used. We introduce the cooperation decision parameter which is only a function of user-to-destination channel qualities and demonstrate that whether cooperation is useful or not depends only on the cooperation decision parameter and not inter-user link quality.

We make use of the analytical formulation of the CDP to explore how user cooperation gain behaves in high signal to noise ratios and how relative link qualities of user-to-user and user-to-destination channels affect cooperation benefits in this asymptotic range. Furthermore, we investigate how one can choose a partner from candidate nodes such that the user cooperation gain is larger. All of our theoretical results are supported by simulations[9]. Further research is required to devise an algorithm that enables the nodes to accrue over time the system information needed to implement the proposed strategies.

### **What is Cooperation**

The Oxford Dictionary define it ‘to cooperate ‘ as ‘to work together act in conjunction (with another person or thing, to end or purpose, or in a work)’.

The broadcast nature of the radio medium may be used to improve the system performance by having a node(s), other than the source and the destination, actively help deliver data frame correctly to the destination. This practice is referred to as cooperative communications.

## **Overview of Vehicular Delay Tolerant Network**

Vehicular delay-tolerant network is a proposal for a DTN-based architecture. It create a communication infrastructure consist of vehicular nodes and fixed nodes, offering a low cost connectivity solution in challenging scenarios where a infrastructure is unreliable. Despite of its rapid growth around the world Internet is still far from becoming universal. Old Internet access is usually not available in remote and populated areas or undeveloped regions. Internet access may also be unavailable due to natural disasters where network infrastructures are vanished [2].

## **Cooperation in Delay Tolerant Networks**

The DTN concept was initially developed for interplanetary networking [5]. However, over the last years, a number of real-world environments where DTN techniques are required have been emerging in the literature.

It is necessary to notice that limited network bandwidth , limited storage capacity and limited energy influence the performance and the capacity of delay tolerant networks. Cooperation is a key issue to the success of data communication in DTN. Where nodes use their storage, bandwidth, and energy resources to mutually enhance the overall network performance

In a cooperative environment, network nodes work together, storing and distributing bundles not only in their own interest, but also in the interest of other nodes. Such a behavior improve the number of transmission paths improving the stornghness to failure of individual nodes[6].

Although cooperation is higly important to improve the capability of network nodes and increasing the overall network performance to the best of out knowledge, little bit research has been done in this field.

The Delay Tolerant Networking paradigm is characterized by the lack of guaranteed connectivity and the typically low frequency of encounters between a given pair of nodes within the network. The routing algorithms proposed for DTNs rely on node mobility for message delivery and may be categorized into single- and multiple-copy algorithms depending on whether they allow the multiplication of the message within the network.

Cooperation has been studied under the framework of peer to- peer and ad-hoc networks. Main issues typically considered are the effect that cooperation might have on the network performance, the detection of non-cooperative behavior, and the design of mechanisms to enforce cooperation. Simple mechanisms have been designed to address cooperation problems, based on game theoretic approaches aiming to provide incentives in order for the nodes to cooperate.

## **Cooperation in Ad-hoc network**

More than a decade the research community has been quite intensivley studying the mobile adhoc networks. Generaly known as MANETs. A greate in size of work has been done towards solving research problems related to wireless ad hoc networks. Although up to greate extent amount of successful research is done, especially when considering military ad hoc networks, the deployment of large-scale ad hoc networks in the civilian context has been limited to very few cases. There are certainly many reasons for this lack of

commercial success, one of those being that the time has not been ripe for ad hoc networking, and certainly many practical engineering problems have been underestimated during the first phase of enthusiasm [4].

In the case of ad hoc networks have to be careful to understand that there are two distinct co-operation domains

1: Communications Cooperation, in the strict communications stack domain, means that we need to provide a common set of communications protocols and transmission methods for all the corresponding hosts so that the network can be established. This problem is shared with all communication systems, but the dynamical nature of the ad hoc networks makes this quite difficult [4].

2: Social Cooperation of the forwarding nodes for a common good is another aspect. There the challenge is the question how to guarantee that nodes between the source and the destination are cooperating on packet forwarding. In the case of the closed ad hoc network applications (such as military or emergency networks) this is easier to ensure than if one is considering highly dynamic privately owned network hosts [4].

Ad hoc networks hold the key to the future of wireless communication, promising adaptive connectivity without the need for expensive infrastructure. In ad hoc networks, the lack of centralized control implies that the behavior of individual users has a profound effect on network performance. For example, by choosing to leave a network or refusing to honor relay requests, a user can severely inhibit communication between other

users. This is a stark contrast with fixed wireless

systems where a single user has much less influence on other users. The influence of user behavior on network performance, in combination with the fact that nodes in an ad hoc network are constrained by their finite energy capacity, motivates the need for a rational and efficient resource allocation scheme [4].

### **Cooperation in Wireless Ad Hoc Networks**

Wireless adhoc have been matured as viable means

to provide ubiquitous communication. In order to enhance network connectivity, a source communication with far off destinations by using intermediate nodes as relays [1].

When applied to singlehop networks, this practice can be embedded into the MAC protocol as follows. The data frame is transmitted by the source to the destination, while a third node(s) — the relay node(s) — overhears the transmission of the data frame and may help improve the delivery success rate over the radio link [12].

The essence of the idea is that, the destination benefits from data frames arriving via two (or more) statistically independent paths, i.e., spatial diversity. The advantages of cooperative communications include the ability to increase the radio link capacity [13] and reduce the latency of automatic retransmission request protocols [14].

### **Cooperation for VDTN**

Vehicular delay tolerant networks also take advantage of the benefits introduced by the cooperative behavior of the network nodes, in order to gain significant enhancement of the network performance. In particular, all VDTN network functions are based on the principle of cooperation between network nodes. Then, for instance, this encompasses the strategies for signaling and resources reservation (e.g, storage and bandwidth).

A large amount of research has been done towards Vehicular Delay Tolerant Network. Although there are still some problems that needs to be solved, we comment certain mature technologies that have emerged. We believe that the major part of the future research work will be directed to new problem domains. In fact, some engineering problems needs to be solved even before intelligent link-aware routing solutions can be implemented easily [4].

### **Conclusion**

Cooperation is a key success for multi agent research system, and such it has received a large amount of intension in the multi agent system literature. However little known about systematic treatments of cooperation structure. In future work we wish to use our framework and algorithms to design the mechanism of punishment and stimulation. In addition, we aim to apply them to electronic commerce [11].

Ad hoc network hold the key to future of wireless communication, promising adaptive connectivity without the need for expansive infrastutrcure.

We would like to emphasize that the aim of this work was to provide a mathematical framework for studying user cooperation in ad hoc networks, and to define strategies leading to an optimal user behavior. Further research is required to devise an algorithm that enables the nodes to accrue over time the system information needed to implement the proposed strategies.

Future research directions on VDTNs may involve the study of bundle assembly and bundle fragmentation mechanisms, enabling congestion control and introducing support for traffic differentiation and ‘quality of service’ routing capabilities.

### **References**

- [1] Jurgen Leitner, ‘Multi-Robot Cooperation in Space: A Survey’. Department of Automation and Systems Technology Helsinki University of Technology, PL 5500, 02015 TKK, Finland.
- [2] Creation of a Vehicular Delay-Tolerant Network Prototype João A. Dias, João N. Isento, Bruno M. Silva, Vasco N. G. J. Soares, Paulo S. Ferreira, António M. D. Nogueira, and Joel J. P. C. Rodrigues Department of Informatics, University of Beira Rua Marques D’Ávila e Bolama – Covilhã, Portugal
- [3] Vehicular Delay Tolerant Network ,Synthesis of the state art of knowledge of the cited architecture, and proposal of VDTN architecture. Jan 1,2009
- [4] T. Jamal and P. Mendes, “Cooperative relaying in user-centric networking under interference conditions,” IEEE Communications Magazine, vol. 52, no. 12, pp. 18–24, dec 2014
- [5] P. Mendes,W. Moreira, T. Jamal and Huiling Zhu, “Cooperative Networking In User-Centric Wireless Networks”, Springer Lecture Notes in Social Networks, User-Centric Networking: Future Perspectives, ISBN 978-3-319- 05217-5, May 2014.
- [6] Cooperation in DTN-Based Network Architectures Vasco N. G. J. Soares, Joel J. P. C. Rodrigues Instituto de Telecomunicações, Portugal

Department of Informatics, University of Beira Interior, Covilhã, Portugal. Superior School of Technology, Polytechnic Institute of Castelo Branco, Portugal.

- [7] V. Rodoplu and T. H. Meng, "Minimum Energy Mobile Wireless Networks," *IEEE Journal on Selected Areas in Communications*, Vol. 17, No. 8, August 1999, pp. 1333–1344.
- [8] T. JAMAL AND P. MENDES. "COOPERATIVE RELAYING FOR DYNAMIC NETWORKS", EU PATENT, (EP13182366.8), AUGUST 2013.
- [9] AN ASYMPTOTIC ANALYSIS ON THE PERFORMANCE OF CODED COOPERATION SYSTEMS, ZINAN LIN ERKIP, E. STEFANOV, A. DEPT. OF ELECTR. & COMPUT. ENG., POLYTECH. UNIV. BROOKLYN, NY, USA.
- [10] Service-Oriented Enterprise Cooperation: Modeling Method and System. 2008 IEEE Asia-Pacific Services Computing Conference. Huiping Lin. Dept. of Service Science & Engineering, Peking University, China linhp@ss.pku.edu.cn  
Sheng Liu Dept. Of Automation, Tsinghua University, China liusheng@tsinghua.edu.cn
- [11] Cooperation Structure of Multi-agent and Algorithms. Li Changhong Institute of System Engineering Tianjin University Tianjin 300072, China 86-022-27408284 LCH7320@sina.com.
- [12] M. Janani, A. Hedyat, T. Hunter, and A. Nosratinia, "Coded Cooperation in Wireless Communications: Space-time Transmission and Iterative Decoding," in *IEEE Trans. on Signal Processing*, Feb 2004, vol. 52, no. 2, pp. 362–371.
- [13] J. N. Laneman, G. W. Wornell, and D. N. C. Tse, "An Efficient Protocol for Realizing Cooperative Diversity in Wireless Networks," in *Proc. IEEE ISIT*, Washington, 2001, p. 294.
- [14] T. Jamal and P. Mendes. Analysis of Hybrid Relaying in Cooperative WLAN. In *Proc. of IFIP WirelessDays*, Valencia, Spain, November 2013.

